



440L Datasheet

Description	"440L" is a medium flow heterophasic polypropylene copolymer with improved mechanical properties balance. The product features high stiffness and outstanding impact strength at low temperatures and is specifically designed for injection molding applications. In comparison with conventional copolymers with the same MFR and same rigidity, "440L", exhibits 35 % higher toughness. "440L" is suitable for a wide range of applications in the packaging, automotive and consumer goods industries. Typical applications include luggage, paint pails, buckets, containers, crates, batteries and large toys.
Processing Method:	Injection molding
Features:	• High impact strength • High stiffness • Heterophasic copolymer
Typical Applications:	Packaging, automotive and consumer goods industries Luggage, paint pails, buckets Containers, crates, batteries and large toys

TYPICAL PROPERTIES	VALUE	UNIT	METHOD
Melt Flow Rate (230 °C, 2.16kg)	6	g/10min	ASTM D1238
Density	0/9	g/cm3	ASTM D1505
Flexural Modulus	1400	MPa	ASTM D790
Tensile Strength at Yield	26	MPa	ASTM D638
Tensile Elongation at Yield	9	%	ASTM D638
Izod Impact Strength (notched) at 23 °C	170	J/m	ASTM D256
Izod Impact Strength (notched) at -20 °C	70	J/m	ASTM D256
Shore hardness (Shore D)	68	----	ISO 868
Vicat softening point (10N)	152	oC	ASTM D1525
H.D.T. (0.46 Mpa)	95	oC	ASTM D648
Accelerated oven ageing in air at 150 °C	360	hours	ASTM D3012



Phone Number : +971586875544



Address : UAE - Dubai - Al Barsha 1 - Rasis Business Center